



## DESCRIPTION

The Velcro Polishing Pad is used with a machine to apply rubbing compound/wax polish. It helps to eliminate paint streaks and sanding scratches. In other words, this product is used to remove all kinds of roughness, scratches and defects on surfaces before polishing.

## USAGE AREA

Velcro Polishing Pad is used to apply wax polish to old or new painted surfaces such as automobile and industrial machinery parts. The product is used with the polishing machine to remove paint streaks and sanding scratches after painting and repair of parts. Velcro Polishing Pad is used in many sectors, especially in the automotive, furniture and fiberglass marine sector.

## USAGE AND APPLICATION

- Velcro Polishing Pad is used by attaching to the base of polishing machine.
- While applying, make sure that the polishing pad does not get caught on the edges and corners of the vehicle.
- Before using the Velcro Polishing Pad, moisten it and make the machine run idle for a short time to drain the water in Velcro Polishing Pad.
- After polishing, clean the Velcro Polishing Pad with water and store them in a nylon package.
- Since it has velcro, it is used with the polishing machine by attaching to the base.
- It is recommended to use between 0-2500 rpm.

## SPECIFICATIONS

- It removes hard scratches and dirt on the surface, helps to eliminate paint streaks and sanding scratches.
- It allows you to get the best efficiency from the surface. Very easy to use and practical.
- Since its absorption degree is low, it spreads the wax polish completely on the surface.
- Velcro Polishing Pad diameter is 200 mm and the product is used by attaching to the base of 200 mm polishing machines.
- It gives an original appearance to the applied surface.

## DIMENSIONS

**Diameter:** 200 mm, **Thickness:** 30 mm (200 mm x 30 mm).

It is also possible to produce Velcro Polishing Pad in different diameters and widths according to demand.